

Red Shield Teflon Tape

Technical Data:

Material: PTFE 99.6%

Pink Pigment: <0.4%

Heat resistance: +350°C

Cold resistance: -268°C

High-pressure resistance 150-200kg/mm2

Percentage elongation >100%

Tensile strength ≥15N/mm2

Residual lubricant ≤0.5%

Tape Color: Pink

Width: 1/2"

Thickness: 0.0035"

Length: 1429"

Density: 0.8g/cm3

UL & ULC listed*

TORONTO HEAD OFFICE (905) 761-6355

Toll Free: (800) 267-8508

Part number: TT-PP





It is inert and compatible with a very wide range of materials. Use it on threads made from galvanized steel, iron, brass, copper, aluminum, stainless steel, polyethylene, polypropylene, PVC, CPVC, ABS, fiberglass and more. It can be used on pipes carrying the following: Acids, concentrated (see precautions) and Acids, dilute

Alcohols, Gasohol

Aliphatic solvents, Aromatic solvents, Chlorinated solvents

Ammonia, liquid

Caustics, concentrated (see precautions) Compressed air, Steam,

Water

Cutting oils

Diesel fuel oil

Ethylene glycol, Glycerine

Fatty acids





Heating oils, Kerosene

Hydraulic fluids, Hydraulic oils

Hydrogen, gaseous and liquid, Inert gases, gaseous and liquid

Jet fuel

Ketones, Petroleum solvents

Liquid Petroleum Gas, Natural gas

Mineral oils, Vegetable oils

Nitrogen, gaseous and liquid

Soap, liquid



*UL/ULC Listed under Fujian Bang-up Fluorine Plastic Product Co. Ltd.

