



**MODEL 201 EXPOSED FIRE DEPARTMENT CONNECTION**

**Model 201, 2 1/2" (65mm) Siamese FD Connection - Straight**



**Application:** Double Inlet FD connection with 500 GPM inlet capacity used to supplement water supply in standpipe or sprinkler systems. Body comes with a single swing clapper to prevent water from exiting the second inlet when not in use.

Body standard with (2) 2 1/2" (65mm) swivel hose thread inlets c/w brass plugs or red aluminum break off caps. Base with 4" (100mm) or 6" (152mm) female NPT. Standard plate lettering is "Auto Spkr", "Standpipe" or combined "Auto Spkr / Standpipe".

**Construction:** Cast brass body with red aluminum plate and caps.

**Rated Pressure:** 300 PSI / 2068.50 kpa

**Approvals:** UL, cUL, FM


UL/cUL Certification #: 20180905-EX27837

FM Approval Id: PR450490

**Thread:** BCT/AMA/WCT/CSA/QST/NSST/NFLD/NST (NH)

**Options:** Satin Chrome, Polished Brass, Polished Chrome

**AMA thread only available in brass finish.**



	INCHES	MM
	4 x 2 1/2	102 x 65
<b>A</b>	5 1/2	139.7
<b>B</b>	8 3/4	222.25