



NATIONAL FIRE EQUIPMENT LTD.

SERVICE, SOLUTIONS, INNOVATION

2.4 Gal. (9L) WATER PORTABLE FIRE EXTINGUISHER



- Polished stainless steel cylinder complete with protective skirt
- Chrome-plated solid brass valve
- Waterproof stainless steel gauge
- Stainless steel handles and siphon tube
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- Shipped empty with out pressure
- Schrader valve for pressurizing
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- Temperature range 4°C to 49°C (40°F to 120°F)

Note: Use of an anti-freeze charge will void the warranty



MODEL	SF-PW250	
CAPACITY	2.4 Gal. (9L)	
UL/ULC RATING	2-A	
U.S.C.G. APPROVAL	N/A	
RANGE	40 ft (12.2 m)	
TEMP. RANGE	4°C to 49°C (40°F to 120°F)	
DISCHARGE TIME	55 sec.	
PSI	100	
HEIGHT	25" (63.5 cm)	
WIDTH	8 3/4" (22 cm)	
DIAMETER	7 1/8" (18 cm)	
WEIGHT (Empty)	7.9 lbs. (3.6 kgs.)	



Made In Canada